

## SHEERWEAVE | 2410 3%



P12 OYSTER




P13 OYSTER/ BEIGE




P14 OYSTER/ PEARL-GRAY



Q20 BEIGE



Q21 BEIGE/ PEARL-GRAY



V20 PEARL/ GRAY



V21 CHARCOAL



V22 CHARCOAL/ GRAY



V24 CHARCOAL/ CHESTNUT



V32 CHARCOAL/ ALPACA

### SPECIFICATION

**WIDTHS** 63", 98" and 126"

**ROLL LENGTH** 30 Linear Yards

**FABRIC WEIGHT** 14.1 oz/yd<sup>2</sup>

**FABRIC THICKNESS** 0.020 in.

**OPENNESS** ~3%

**UV BLOCKAGE** ~97%

**COMPOSITION** 36% Fiberglass, 64% Vinyl on Fiberglass

**ACOUSTICAL VALUE** NRC .20 / SAA .21

**PRINTABLE** Yes

**FIRE CLASSIFICATION** NFPA 701 TM#1 (small scale) TM#2 (large scale)  
 NFPA 101 (Class A Rating)  
 California U.S. Title 19 (small scale)  
 BS 5867 Part 2 Type B Performance  
 CAN/ULC-S 109 (large and small scale)  
 CAN/CGSB2-4.162-M80  
 IBC Section 803.1.1 (Class A Rating)

**BACTERIA/ FUNGAL RESISTANCE** ASTM E 2180 ASTM G21 AATCC30 Part 3 ASTM D 3273 ASTM G22 GREENGUARD Mold and Bacteria Standard ASTM 6329 includes Microban antimicrobial additives

**LEAD FREE** RoHS/Directive 2002/95/EC REACH (EC 1907/2006) compliant ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101

**WARRANTY** 10-Year (Interior), 5-Year (Exterior)

