



SHEERWEAVE | PERFORMANCE 2410+ 3% Metallized Fabric




P12 OYSTER



P13 OYSTER/ BEIGE



P14 OYSTER/ PEARL-GRAY




Q20 BEIGE



Q21 BEIGE/ PEARL-GRAY



V20 PEARL/ GRAY



V21 CHARCOAL



V22 CHARCOAL/ GRAY



V24 CHARCOAL/ CHESTNUT



V32 CHARCOAL/ ALPACA

SPECIFICATION

WIDTHS 63" and 96"
ROLL LENGTH 30 Linear Yards
FABRIC WEIGHT 14.1 oz/yd²
FABRIC THICKNESS 0.019 in.
OPENNESS ~3%
UV BLOCKAGE ~97%
COMPOSITION 37% Fiberglass, 63% Vinyl on Fiberglass
 2% Aluminum Coating
ACOUSTICAL VALUE NRC .25 / SAA .23
PRINTABLE No

FIRE CLASSIFICATION California U.S. Title 19 (small scale) NFPA 701 TM#1 (small scale) TM#2 (large scale)
 NFPA 101 (Class A Rating) IBC Section 803.1.1 (Class A Rating) BS 5867 Part 2 Type B Performance
 NFPA 701 CAN/ULC-S 109-03 (large and small scale) CAN/CGSB2-4.162-M80
 M1 (NF-P-92 503) B2 (DIN 4102-1)

BACTERIA/ FUNGAL RESISTANCE ASTM E 2180 ASTM G21 AATCC30 Part 3 ASTM D 3273 ASTM G22 GREENGUARD Mold and Bacteria Standard ASTM 6329 includes Microban antimicrobial additives

LEAD FREE RoHS/Directive 2002/95/EC REACH (EC 1907/2006) compliant ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101

WARRANTY 5-Year (Interior)

