


SHEERWEAVE | PERFORMANCE 2500+ 1% Metallized Fabric



P12 OYSTER



P13 OYSTER/ BEIGE




P14 OYSTER/ PEARL-GRAY




Q20 BEIGE



Q21 BEIGE/ PEARL-GRAY



V20 PEARL/ GRAY



V21 CHARCOAL



V22 CHARCOAL/ GRAY



V24 CHARCOAL/ CHESTNUT



V32 CHARCOAL/ ALPACA

SPECIFICATION

WIDTHS	63" and 96"
ROLL LENGTH	30 Linear Yards
FABRIC WEIGHT	16.39 oz/yd ²
FABRIC THICKNESS	0.024 in.
OPENNESS	~1%
UV BLOCKAGE	~99%
COMPOSITION	38% Fiberglass, 62% Vinyl on Fiberglass 2% Aluminum Coating
ACOUSTICAL VALUE	NRC .50 / SAA .49
PRINTABLE	No

FIRE CLASSIFICATION California U.S. Title 19 (small scale) NFPA 701 TM#1 (small scale) TM#2 (large scale)
NFPA 101 (Class A Rating) IBC Section 803.1.1 (Class A Rating) BS 5867 Part 2 Type B Performance
NFPA 701 CAN/ULC-S 109-03 (large and small scale)
CAN/CGSB2-4.162-M80
M1 (NF-P-92 503) B2 (DIN 4102-1)

BACTERIA/ FUNGAL RESISTANCE ASTM E 2180 ASTM G21 AATCC30 Part 3 ASTM D 3273 ASTM G22 GREENGUARD Mold and Bacteria Standard ASTM 6329 includes Microban antimicrobial additives

LEAD FREE RoHS/Directive 2002/95/EC REACH (EC 1907/2006) compliant ANSI/WCMA A 100.1-2007 for lead content
US Consumer Product Safety Commission Section 101

WARRANTY 5-Year (Interior)

