


## SHEERWEAVE | 2703 3% Dual Sided



### SPECIFICATION

<p><b>WIDTHS</b> 63", 98" and 126"</p> <p><b>ROLL LENGTH</b> 30 Linear Yards</p> <p><b>FABRIC WEIGHT</b> 14.0 oz/yd<sup>2</sup></p> <p><b>FABRIC THICKNESS</b> 0.028 in.</p> <p><b>OPENNESS</b> ~3%</p> <p><b>UV BLOCKAGE</b> ~97%</p> <p><b>COMPOSITION</b> 36% Fiberglass, 64% Vinyl on Fiberglass</p> <p><b>ACCOUSTICAL VALUE</b> NRC .10 / SAA .09</p> <p><b>PRINTABLE</b> Yes</p>	<p><b>FIRE CLASSIFICATION</b> NFPA 701 TM#1 (small scale) TM#2 (large scale)          NFPA 101 (Class A Rating)          California U.S. Title 19 (small scale)          BS 5867 Part 2 Type B Performance          CAN/ULC-S 109 (large and small scale)          CAN/CGSB2-4.162-M80          IBC Section 803.1.1 (Class A Rating)</p> <p><b>BACTERIA/ FUNGAL RESISTANCE</b> ASTM E 2180 ASTM G21 AATCC30 Part 3 ASTM D 3273 ASTM G22 GREENGUARD Mold and Bacteria Standard ASTM 6329 includes Microban antimicrobial additives</p> <p><b>LEAD FREE</b> RoHS/Directive 2002/95/EC REACH (EC 1907/2006) compliant ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101</p> <p><b>WARRANTY</b> 10-Year (Interior), 5-Year (Exterior)</p>
--	---

