



## SHEERWEAVE | 4550 5%




P10 GRANITE



P65 LINEN



V45 COAL



V47 CHESTNUT

### SPECIFICATION

<b>WIDTHS</b> 63" and 98"	<b>BACTERIAL AND RESISTANCE</b>	ASTM E 2180, ASTM G21, ASTM G22, AATCC30
<b>ROLL LENGTH</b> 30 Linear Yards	<b>ACOUSTICAL PERFORMANCE</b>	Part 3, ASTM D 3273
<b>FABRIC WEIGHT</b> 13.00 oz/yd <sup>2</sup>	<b>ENVIRONMENTAL BENEFITS</b>	NRC 0.15 / SAA 0.18
<b>FABRIC THICKNESS</b> 0.025 in.	<b>FIRE CLASSIFICATION</b>	Certified to GREENGUARD and GREENGUARD Gold
<b>OPENNESS</b> ~5%		California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), NFPA 101 (Class A Rating), IBC Section 803.1.1 (Class A Rating), BS 5867 Part 2 Type B Performance, NFPA 701 TM#2 (large scale), CAN/ULC-S 109 (large and small scale)
<b>UV BLOCKAGE</b> ~95%		
<b>COMPOSITION</b> 17% Polyester, 83% Vinyl on Polyester		
<b>WARRANTY</b> 5-Years Interior, 10- Years Exterior		



### Care & Handling

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or a soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the blind down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.