

SHEERWEAVE | 7750 R LIGHTFILTERING



TB1 CRYSTAL



TB2 SAND



TB4 CHALK



TB3 CONCRETE



TB5 GRAPHITE



TB6 PEWTER



TB7 ONYX

SPECIFICATION

WIDTHS 118"

ROLL LENGTH 22 Linear Yards

FABRIC WEIGHT 8.80 oz/yd²

FABRIC THICKNESS 0.023 in.

OPENNESS Light-Filtering

COMPOSITION 100% Polyester with Acrylic Coating

WARRANTY 5- Years Interior

**BACTERIAL AND
RESISTANCE
ENVIRONMENTAL
BENEFITS
FIRE CLASSIFICATION**

ASTM G21, AATCC 174-1998 Part II and III

Certified to GREENGUARD

Style 7750R: California Technical Bulletin 117,
NFPA 101 (Class A Rating), IBC Section 803.1.1
(Class A Rating)



Care & Handling

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or a soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the blind down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.