




Infinity2 5%




PG1 COTTON



PG2 ALMOND




PG3 WHEAT




PG4 STONE



QG1 BARLEY



VG1 NICKEL



VG2 MIDNIGHT



VG3 BARK



VG4 SLATE

SPECIFICATION

WIDTHS 63" and 98"	BACTERIAL AND RESISTANCE	ASTME 2180, ASTM G21
ROLL LENGTH 30 Linear Yards	ACOUSTICAL PERFORMANCE	NRC 0.10 / SAA 0.11
FABRIC WEIGHT 12.82 oz/yd ²	ENVIRONMENTAL BENEFITS	Certified to GREENGUARD and GREENGUARD Gold
FABRIC THICKNESS 0.030 in.	FIRE CLASSIFICATION	NFPA 701 TM#1 (small scale), NFPA 101 (Class A Rating), CAN/ULC-S 109 (large scale), IBC Section 803.1.1 (Class A Rating), BS 5867 Part 2 Type B Performance, CAN/CGSB 2-4.162-M80
OPENNESS ~5%		
UV BLOCKAGE ~95%		
COMPOSITION 100% Thermoplastic Olefin, 20% TPO Fiber Yarn/80% TPO Coating on TPO Yarn		
WARRANTY 5-Years Interior		



Care & Handling

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or a soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the blind down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.